



MK series professional cinema speakers

2-way 2-component horn tweeter design, horn curve after careful design.

The horn is laminated with Finnish birch board, accurately cut with CNC lathe, and polished and painted for many times.

However, due to the mild and suitable resonance characteristics of birch multilayer board, it can greatly reduce the adverse interference caused by acoustic vibration on the horn.

The timbre is more mellow and pleasant than the general ABS plastic or metal horn.



MK-08 Specification

• Driver components	1.4"Horn Driver×1 8"Midrange Woofer×1
• Frequency	70-20000Hz±3dB
• Impedance	8Ω
• Power Handling	150W
• Sensitivity	93dB
• Max SPL	118dB
• Dimensions	440(H)*304(W)*229(D)mm
• Shipping dimensions	515(H)*385(W)*320(D)mm
• Net weight	11KG/each
• Shipping weight	13KG/each

MK-10 Specification

• Driver components	1.4"Horn Driver×1 10"Midrange Woofer×1
• Frequency	60-20000Hz±3dB
• Impedance	8Ω
• Power Handling	250W
• Sensitivity	95dB
• Max SPL	120dB
• Dimensions	550(H)*380(W)*249(D)mm
• Shipping dimensions	625(H)*475(W)*330(D)mm
• Net weight	17.8KG/each
• Shipping weight	20KG/each

